HOW TO ORDER

STANDARD DC MOTOR HYDRAULIC POWER PACKS (W800532 STEEL MANIFOLD / ∅140 & ∅180 TANKS)

MOTOR TEMP. PROTECTOR	DC MOTOR	MOUNTING POSITIONS	TANK SIZE	LOWERING VALVE	PUMP CAPACITY	HANDLE PUMP	START SWITCH POSITIONS	BREATHER CAP POSITIONS	FLOW CONTROL VALVE	UNIQUE CODE
T	C N 2 4	H	10	S	10		A	A	N	D ***

T	WITH TEMPERATURE PROTECTOR
	WITHOUT TEMPERATURE PROTECTOR

H	HORIZONTALLY MOUNTED
V	VERTICALLY MOUNTED
X	SPECIAL MOUNTING
HN	HORIZONTALLY MOUNTED WITHOUT TANK
VN	VERTICALLY MOUNTED WITHOUT TANK

S	SOLENOID OPERATED (NORMALLY CLOSED)
T	SOLENOID OPERATED (NORMALLY OPEN)
U	SOLENOID OPERATED (NORMALLY CLOSED WITH MANUAL)
V	SOLENOID OPERATED (NORMALLY OPEN WITH MANUAL)
MR	MANUAL OPERATED
MK	MANUAL OPERATED (WITHOUT SWITCH)
N	NONE
X	SPECIAL OPERATED
A	ADAPTOR FOR OTHER MANIFOLD

A	SAME SIDE AS CHECK VALVE
B	SAME SIDE AS RELIEF VALVE
C	THE SIDE OPPOSITE A
D	THE SIDE OPPOSITE B
N	NONE

N	NONE
2	2 LPM
4	4 LPM
6	6 LPM
8	8 LPM
10	10 LPM

rated flows

	WITHOUT HANDLE PUMP
P	WITH HANDLE PUMP (7.4cc/stroke)
X	SPECIAL HANDLE PUMP ASSEMBLY

2				550W LOW-SPEED MOTOR
3				800W COMPOUND WOUND MOTOR
5				550W PERMANENT MAGNET MOTOR
8				800W PERMANENT MAGNET MOTOR
C				2000W COMPOUND WOUND MOTOR (DC24V) 1500W COMPOUND WOUND MOTOR (DC12V)
S				2000W SERIES WOUND MOTOR (DC24V) 1500W SERIES WOUND MOTOR (DC12V)
L				3000W COMPOUND WOUND MOTOR (DC24V) 2500W COMPOUND WOUND MOTOR (DC12V)
	E			EARTH RETURN (MOTOR WITH 1 TERMINAL)
	N			INSULATE RETURN (MOTOR WITH 2 TERMINALS)
		1	2	DC12V MOTOR
		2	4	DC24V MOTOR
N	N	N	N	WITHOUT MOTOR
X	X	X	X	SPECIAL
P				2200W COMPOUND WOUND MOTOR (DC24V) 1600W COMPOUND WOUND MOTOR (DC12V)

∅140 mm Dia.	10	1.0 Liters
	16	1.6 Liters
	20	2.0 Liters
	24	2.4 Liters
	28	2.8 Liters
	42	4.2 Liters
∅180 mm Dia.	30	3.0 Liters
	40	4.0 Liters
	50	5.0 Liters
	60	6.0 Liters
	80	8.0 Liters
	XX	SPECIAL
	NN	NONE

(working volume)

05	0.5 cc/rev
07	0.7 cc/rev
10	1.0 cc/rev
15	1.5 cc/rev
19	1.9 cc/rev
23	2.3 cc/rev
27	2.7 cc/rev
30	3.0 cc/rev
35	3.5 cc/rev
40	4.0 cc/rev
51	5.1 cc/rev
62	6.2 cc/rev
73	7.3 cc/rev

	MANIFOLD FUNCTION A-Z
	STANDARD MANIFOLD
D	STANDARD MANIFOLD WITH LOW NOISE RELIEF VALVE

Special orders are available on request.
Please consult our sales department.

Hydraulic Power Packs

Series W80D