



### TECHNICAL DATA

Aluminum Body Pressure Rating: 210 bar  
 Ductile Iron Body Pressure Rating: 350 bar

### Cavity:

Refer to 12W2

\* Refer to Winner Cartridge Valves Catalog.

Aluminum	0.51 kg(WITHOUT VALVES)
Ductile Iron	1.5 kg(WITHOUT VALVES)

\* If you need the special specification. Please contact us.

X	PORT SIZE		
	PORT	PORT	
	1	2	
G06	G 3/4"	G 3/4"	
P03	3/8"PT	3/8"PT	
P04	1/2"PT	1/2"PT	
S08	SAE 8	SAE 8	
S10	SAE 10	SAE 10	

Y	BODY MATERIAL	
A	HIGH-STRENGTH ALUMINUM	
S	DUCTILE IRON	

Z	CARTRIDGE VALVES SELECTION	
	WITHOUT VALVE	
CV03	CV12W2003N (90LPM,0.3bar)	
NV0N	NV12W20NL (350bar)	
EP01	EP12W2A01N05 , 150LPM,350bar (NORMALLY CLOSED,WITHOUT COIL)	
EP02	EP12W2A02N05 , 150LPM,350bar (NORMALLY OPEN,WITHOUT COIL)	

COIL MUST BE ORDERED SEPARATELY  
(REFER TO EC-04W-X-Y-Z)

The selection is only example. Please refer to Winner Cartridge Program and to select the appropriate valves and manifolds assembly in accordance with request function (flow 、 pressure 、 ... etc.)