



### TECHNICAL DATA

Aluminum Body Pressure Rating: 210 bar  
Ductile Iron Body Pressure Rating: 350 bar

Cavity:  
Refer to 17A3  
08W2

\* Refer to Winner Cartridge Valves Catalog.

Aluminum	1.45 kg(WITHOUT VALVES)

\* If you need the special specification. Please contact us.

<b>X</b>	<b>CARTRIDGE VALVES SELECTION</b>	
<b>17A3</b>	CAVITY ONLY(WITHOUT VALVE)	
<b>RV0A</b>	RV17A30AL (240LPM , 7-210bar)	

The selection is only example. Please refer to Winner Cartridge Program and to select the appropriate valves and manifolds assembly in accordance with request function (flow 、 pressure 、 ... etc.)

<b>Y</b>	<b>SELECTION FOR SOLENOID VALVES (REFER TO EP08W-X-Y-Z)</b>	
<b>08W2</b>	CAVITY ONLY(WITHOUT VALVE)	
<b>EP02</b>	EP08W2A02N04 , 30LPM,350bar (NORMALLY OPEN,WITHOUT COIL)	
<b>COIL MUST BE ORDERED SEPARATELY (REFER TO EC-04W-X-Y-Z)</b>		
The selection is only example. Please refer to Winner Cartridge Program and to select the appropriate valves and manifolds assembly in accordance with request function (flow 、 pressure 、 ... etc.)		

	<b>PORT SIZE</b>		
<b>Z</b>	<b>PORTS</b>	<b>PORT</b>	
	<b>1,2</b>	<b>G</b>	
<b>G08</b>	G 1"	G 1/4"	